

# Panasonic

ideas for life

## KX-FLB851



- Flexible 3-Bin Sorter
- Up to 18 ppm Print Speed
- 600 x 600 dpi Print Resolution
- Up to 18 cpm Copy Speed
- 33.6 kbps Fax Modem
- Flatbed Colour Scanner



**LASER**

**Multi-Function**

## Options



KX-FLB851 with KX-FA101X



KX-FA101X Lower Input Tray (500 sheets)



KX-FA102X LAN Board



KX-FA103X Handset Unit

## Consumables

KX-FA85X  
Toner Cartridge (5,000 pages)\*2,\*6  
KX-FA86X  
Drum Unit (Max. 10,000 pages)\*7

## Service Parts

KX-FA104X Maintenance Kit

## KX-FLB851 Specifications

### General Function

Type:	Desktop
Printing Process:	Laser
Flexible Sorter:	Flexible 3 bins
Multi-Purpose Tray:	30 sheets
Standard Memory Capacity:	32 MB
PC Interface:	USB 2.0
Scanning System:	CCD image sensor, fixed flatbed
Caller ID Ready*4	FSK
Dialing Mode:	Tone/pulse
Automatic Document Feeder:	50 sheets
Paper Tray:	250 sheets
Multi-Purpose Tray:	30 sheets
Optional Tray:	500 sheets
Warmup Time:	Approx. 15 seconds (20°C)

### Printer Function

PC Interface:	USB 2.0
Printing Speed:	18 PPM
Printing Resolution:	600 dpi x 600 dpi
Compatible OS:	98/Me/2000/XP
Emulation:	GDI
Paper Handling:	A4/letter/envelope

### Copier Function

First Copy Time:	Approx. 17 seconds (A4)
Memory Copy Speed:	18 CPM
Resolution:	600 dpi x 600 dpi
Multi-Copy:	Up to 99 copies
Zoom (variable):	50 - 200% in 5% increments
Collate:	Sorter function

### Fax Function

Compatibility:	ITU T G3
Paper Handling:	A4
Scanning Width:	208 mm
Modem Speed:	33.6 kbps with automatic fallback
Transmission Speed:	Approx. 4 seconds per page*2,*6 in ECM-MMR memory transmission
Compression System:	MH / MR / MMR
Resolution:	Standard/fine/super fine/halftone
Halftone:	64 levels
Memory Transmission:	Max. 150 pages*3
Memory Reception:	Max. 630 pages*3

### Scanner Function

Colour Scanning:	Input 48 bits, output 24 bits
Monochrome Scanning:	Input 16 bits, output 8 bits
Scanning Resolution:	600 dpi x 600 dpi (ADF) 600 dpi x 1200 dpi (Flat-Bed) 9600 dpi x 9600 dpi (interpolated)
Scanner Driver:	TWAIN 18

### Network Compatibility (Option)

Optional LAN Board:	KX-FA102X
Network Connectivity:	10BASE-T/100BASE-TX
Network Operation:	Printer, Scan-to-PC

### Power Consumption:

Standby:	Approx. 11 W
Transmission:	Approx. 28 W
Reception:	Approx. 400 W
Copy:	Approx. 430 W
Maximum:	Approx. 900 W when the fuser lamp turns on
Power Source:	AC 220 - 240V, 50/60 Hz
Dimensions (W x D x H):	773 mm x 444 mm x 312 mm
Weight:	Approx. 18.0 kg

\*1 When the optional LAN Board (KX-FA102) is connected

\*2 Based on ITU-T No.1 test chart.

\*3 Max. 630 pages for out-of-paper reception. Max. 150 pages for memory transmission.

\*4 Requires subscription to fee-based phone company service.

\*5 Available when connected to PC running Microsoft® Windows® 98/Me/2000/XP. Multi-function software is included.

\*6 5% coverage

\*7 The drum longevity is tested by 20-sheet continued printout intervals.

Microsoft and Windows are registered trademarks of Microsoft Corporation in the United States and/or other countries.

# Panasonic®

Global Web Sites: <http://www.panasonic.co.jp/global>

Design and specifications are subject to change without notice. 0M0206UA-KX-FLB851-LT.EEU